

AR70 AND AR111 PRO



Product fully developed by Stella.

One-piece body providing clean, seamless design.

Thinner edge.

Floating deflector that reduces glare.

Candela value up to 4 times higher than the current AR EVO from the Stella line

Color temperatures 2700K, 3000K and 4000K.







Opening angle for AR70 of 7°, 14° and 24°.

Opening angle for AR111 of 6°, 10° and 24°



AR70 AND AR111 PRO



ARs PRO						
Parameter						
	AR70 PRO 7°	AR70 PRO 14°	AR70 PRO 24°	AR111 PRO 6°	AR111 PRO 10°	AR111 PRO 24°
Luminous flux (lm)	250lm	300lm	320lm	540lm	720lm	740lm
Color temperature (K)	2700K	2700K / 3000K	2700K / 3000K / 4000K	2700K	2700K / 3000K	2700K / 3000K / 4000K
CRI	>95	>95	>95	>95	>95	>95
Power (W)	4,7W	4,7W	4,7W	11W	11W	11W
Efficiency (lm/W)	53lm/W	64lm/W	68lm/W	49lm/W	65lm/W	67lm/W
Angle (°)	7°	14°	24°	6°	10°	24°
Candelas (cd)	8.200cd	3.450cd	1.850cd	25.500cd	13.800cd	3.550cd



AR70 AND AR111 PRO

